



LaBounty®

URL:<http://www.maruma.co.jp>

**SHEARS HAVE NEVER
BEEN MORE PRODUCTIVE**

MSD ラバウンティシア レジェンドシリーズ

A NEW LEGEND - FORGED IN INNOVATION

The goal was simple - minimize maintenance and increase performance.
The result-maximized productivity and uptime.

We are proud to introduce the Legend Series Mobile shear featuring the Dual
MAX™ piercing tip, the industry's only full-protection, indexable mobile shear tip.

MARUMA TECHNICA

NEW FOR 2020

LaBounty®

MSD LEGEND SERIES A NEW LEGEND- FORGED IN INNOVATION

我々は自信をもってこのレジェンドシリーズを導入します

シンプルな目的 - 最小限のメンテナンス

- 生産性向上

大きな結果

- 最大限の生産性

- 稼働時間の増加

旋回ロック

デュアルマックスチップ

ウェアバー

360°油圧全旋回及びバランス向上

ロアジョー構造強化

ENHANCEMENTS




デュアルマックスチップ

反転2面使用可能
ジョー部全面保護
質量軽減・ロングライフ



切断力 UP

アッパージョー形状変更による
切断力アップ (中間部)
前モデル比 5 ~ 10% アップ



ブレード反転・交換容易化

アッパージョー用・ロワジョー用それぞれ専用
ブレードの採用による反転・交換
の容易化

SPECIFICATIONS

【固定タイプ】

モデル	装着油圧ショベル ブーム取付 (t)	シア質量 (含 ブラケット) (kg)	開口幅 (mm)	奥行 (mm)
MSD1500-L	12	3,200	540	640
MSD2000-L	20	4,250	710	740
MSD2500-L	22	5,750	790	840
MSD3000-L	30	6,450	860	940
MSD4500-L	40	8,550	990	1,090

【旋回タイプ】

モデル	装着油圧ショベル ブーム取付 (t)	シア質量 (含 ブラケット) (kg)	開口幅 (mm)	奥行 (mm)
MSD1500R-L	20	3,400	540	640
MSD2000R-L	22	5,000	710	740
MSD2500R-L	30	6,950	790	840
MSD3000R-L	40	8,100	860	940
MSD4500R-L	60	10,050	990	1,090

○標準的なブラケットを取付した場合の質量となります。また追加オプション等の質量は含まれておりません。

○ブラケットの形状によって±5%程度質量が変化することがあります。

○本機は改良のため、予告なく仕様変更することがありますので予めご了承ください。

○掲載写真は一部販売車と異なる場合があります。また、ディーラオプションが一部含まれています。

○掲載写真はカタログ撮影用のものがあります。機械を離れる際は作業機を接地される等 安全に留意してください。

○本機をご利用される際は必ず取扱説明書をよくお読みください。

○機体質量3トン以上の建設機械の運転には「車輦系建設機械運転技能講習修了証」の取得が必要です。

○本アタッチメントを使用する場合、車輦系建設機械運転技能講習修了証【(整地・運搬・積込用及び掘削用)及び(解体用)】が必要となります。

日本総代理店

ママルマテクニカ株式会社
MARUMA TECHNICA CO., LTD.

名古屋事業所 愛知県小牧市小針2丁目18番地 〒485-0037
電話 (0568) 77-3312 FAX. (0568) 77-3719

本社・相模原事業所
厚木工場 神奈川県厚木市小野651番地 〒243-0125
電話 (046) 250-2211 FAX. (046) 250-5055

東京工場 東京都世田谷区桜丘1丁目2番22号 〒156-0054
電話 (03) 3429-2141 FAX. (03) 3420-3336

URL: <http://www.maruma.co.jp> E-mail: n-apl@maruma.co.jp

STANLEY

LaBounty®

ISO9001:2008 認証取得



3031-3031-01 191240